



(43) International Publication Date
10 June 2004 (10.06.2004)

PCT

(10) International Publication Number
WO 2004/049260 A2

(51) International Patent Classification⁷: **G06T 7/20**

(21) International Application Number:
PCT/GB2003/005007

(22) International Filing Date:
18 November 2003 (18.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0227566.7 26 November 2002 (26.11.2002) GB

(71) Applicant (for all designated States except US): **BRITISH TELECOMMUNICATIONS PUBLIC LIMITED COMPANY** [GB/GB]; 81 Newgate Street, London EC1A 7AJ (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **LI, Yongmin** [CN/GB]; 167 Cavendish Street, Ipswich, Suffolk IP3 8BG (GB). **XU, Li-Qun** [GB/GB]; 34 Dodson Vale,

Kesgrave, Suffolk IP5 2GT (GB). **MORRISON, David, Geoffrey** [GB/GB]; 10 Tylers Green, Trimley, Felixstowe, Suffolk IP11 0XF (GB). **NIGHTINGALE, Charles** [GB/GB]; 39 Quilter Road, Felixstowe, Suffolk IP11 7JL (GB). **MORPHETT, Jason** [GB/GB]; Valley View, 41 Holton Road, Halesworth, Suffolk IP19 8HG (GB).

(74) Agent: **WALLIN, Nicholas, James**: BT Intellectual Property Department, PPC5A, BT Centre, 81 Newgate Street, London EC1A 7AJ (GB).

(81) Designated States (national): CA, US.


(84) Designated States (regional): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND SYSTEM FOR ESTIMATING GLOBAL MOTION IN VIDEO SEQUENCES



(57) Abstract: The invention relates to estimating the global motion between frames of a motion-compensated inter-frame encoded video sequence, directly from the motion vectors encoded within the frames. For any particular frame, a motion estimation is determined from motion vectors direct from the frame's anchor frame to the frame in question. This motion estimation is then checked against pre-determined criteria, and where the criteria are not met, re-estimation along a different route is performed, using the bi-directional motion vectors contained within B-frames. A panoramic image generating method and system which makes use of the global motion estimations thus obtained is also described.